

# TECHNICAL DATASHEET

# 568010102

Rev.00



## FEATURES:

- Economic spectacle ideal for essential protection
- Lightweight and handy, entirely made of polycarbonate, weighs only 23 grams
- Available the version certified to small faces (568.01.00.00H)
- Highly suitable for customization

## FRAME FEATURES:

|                   |                       |
|-------------------|-----------------------|
| Frame Typology    | <b>Spectacle</b>      |
| PPE field of view | <b>&gt;40°</b>        |
| Temple adjustment | -                     |
| Weight (g)        | <b>23</b>             |
| Size (mm)         | <b>134 □ 15 X 116</b> |
| Material Features | <b>Anallergic</b>     |

## FEATURES OCULARS/LENSES:

|                         |                       |
|-------------------------|-----------------------|
| Ocular/Flip-up Material | <b>Polycarbonate</b>  |
| Colour                  | <b>Smoke</b>          |
| Technical Treatment     | <b>Antiscratch</b>    |
| Aesthetic Treatment     | -                     |
| Thickness [mm](+/- 0.1) | <b>2.3</b>            |
| Curvature               | <b>Base 9 Spheric</b> |
| Optical Class           | <b>1</b>              |
| UV Protection           | <b>380 nm</b>         |
| Spare Parts             | -                     |
| VLT% (+/-5%)            | <b>14</b>             |

## MARKING DATA:

|                        |                              |
|------------------------|------------------------------|
| Standard References    | <b>EN166 EN170 EN172</b>     |
| Frame Marking          | <b>Mod.568 U EN166 FT CE</b> |
| Ocular/Flip-up Marking | <b>2C-3/5-3.1 U 1 FT CE</b>  |

## APPLICATION FIELDS

**Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T)**

Notes

